



Kloubová oka s vnějším závitem

TSM
TSM...C

Ekvivalent SKF
SAKAC...M

Ekvivalent INA
GAK FR...PB
GAK FR...PW

Typ	Rozměry [mm]									Zatížení [kN]		Hmot. [Kg]
	d	d ₁	B ₁	E	B	D	S	L ₁	L ₂	Dynamic	Static	
TSM5	5	7.7	8	11.11	7	16	M5x0.8	33	20	3.2	7	0.014
TSM6	6	9	9	12.70	7	18	M6x1	36	22	3.5	8	0.019
TSM8	8	10.4	12	15.88	9	22	M8x1.25	42	25	5.8	13	0.036
TSM10	10	12.9	14	19.05	11	26	M10x1.5	48	29	8.6	18	0.060
TSM12	12	15.4	16	22.23	12	30	M12X1.75	54	33	11.5	24	0.089
TSM14	14	16.9	19	25.40	14	34	M14x2	60	36	17.5	36	0.129
TSM16	16	19.4	21	28.58	15	38	M16x2	66	40	20	40	0.181
TSM17	17	20.6	22	30.16	16	40	M16x1.5	69	42	22	45	0.206
TSM18	18	21.9	23	31.75	17	42	M18x1.5	72	44	27	50	0.250
TSM20	20	24.4	25	34.93	18	46	M20X1.5	78	47	31	60	0.333
TSM22	22	25.9	28	38.10	20	50	M22x1.5	84	51	43	72	0.430
TSM25	25	29.5	31	42.86	22	56	M24x2	94	57	50	85	0.575
TSM28	28	32.3	35	47.59	25	66	M27x2	103	62	60	90	0.800
TSM30	30	34.9	37	50.80	26	67	M30x2	110	66	66	110	0.996

Uložení ocel/bronz

Typ	Rozměry [mm]									Zatížení [kN]		Hmot. [Kg]
	d	d ₁	B ₁	E	B	D	S	L ₁	L ₂	Dynamic	Static	
TSM5C	5	7.7	8	11.11	7.5	18	M5	33	20	3.2	7	0.014
TSM6C	6	8.9	9	12.70	7.5	20	M6	36	22	3.5	8	0.019
TSM8C	8	10.3	12	15.88	9.5	24	M8	42	25	5.8	13	0.036
TSM10C	10	12.9	14	19.05	11.5	30	M10	48	29	8.6	18	0.070
TSM12C	12	15.4	16	22.23	12.5	34	M12	54	33	11.5	24	0.110
TSM14C	14	16.8	19	25.40	14.5	38	M14	60	36	17.5	36	0.130
TSM16C	16	19.3	21	28.58	15.5	42	M16	66	40	20	40	0.220
TSM18C	18	21.8	23	31.75	17.5	46	M18x1.5	72	44	27	50	0.290
TSM20C	20	24.3	25	34.93	18.5	50	M20X1.5	78	47	31	60	0.360
TSM22C	22	25.8	28	38.10	21	56	M22x1.5	84	51	43	72	0.490
TSM25C	25	29.5	31	42.86	23	60	M24x2	94	57	50	85	0.650
TSM28C	28	32.2	35	47.59	26	66	M27x2	103	62	60	90	0.870
TSM30C	30	34.8	37	50.80	27	70	M30x2	110	66	66	110	1.060

Uložení ocel/PTFE - bezúdržbové